


Communication Networks

Spring 2021



Laurent Vanbever

nsg.ee.ethz.ch

ETH Zürich (D-ITET)

May 17 2021

Materials inspired from Scott Shenker & Jennifer Rexford

Last week on
Communication Networks

TCP: Reliable, in-order delivery

TCP provides a **connection-oriented, reliable, bytestream** transport service


What UDP provides, plus:

- Retransmission of lost and corrupted packets
- Flow control (to not overflow receiver)
- Congestion control (to not overload network)
- “Connection” set-up & tear-down

TCP Header

Source port		Destination port	
Sequence number			
Acknowledgment			
HdrLen	0	Flags	Advertised window
Checksum		Urgent pointer	
Options (variable)			
Data			

Establishing a TCP Connection



Each host tells its ISN to the other host.

Three-way handshake to establish connection

- Host A sends a **SYN** (open; “synchronize sequence numbers”)
- Host B returns a SYN acknowledgment (**SYN ACK**)
- Host A sends an **ACK** to acknowledge the SYN ACK

This week on
Communication Networks

Congestion
Control



DNS

ethz.ch ➡
129.132.19.216

Introduction to
2nd project

reliable transport
starts *today!*

Congestion
Control

DNS

Introduction to
2nd project



Congestion
Control

DNS

Introduction to
2nd project

ethz.ch ➡
129.132.19.216

Internet has one global system for

- addressing hosts IP
by design
- naming hosts DNS
by "accident", an afterthought

Internet has one global system for

- naming hosts DNS

by "accident", an afterthought


Using Internet services can be divided into four logical steps

step 1	A person has name of entity she wants to access	www.ethz.ch
step 2	She invokes an application to perform the task	Chrome
step 3	The application invokes DNS to resolve the name into an IP address	129.132.19.216
step 4	The application invokes transport protocol to establish an app-to-app connection	

The DNS system is a distributed database
which enables to resolve a name into an IP address



In practice,
names can be mapped to more than one IP



In practice,
IPs can be mapped by more than one name

name	DNS	IP address
www.ethz.ch		129.132.19.216
www.vanbever.eu		82.130.102.71
www.route-aggregation.net		82.130.102.71
comm-net.ethz.ch		82.130.102.71

How does one resolve a name into an IP?

initially

all host to address mappings
were in a file called hosts.txt

in /etc/hosts

problem

scalability in terms of query load & speed
management

consistency

availability

When you need... more flexibility,
you add... a layer of indirection

When you need... more scalability,
you add... a hierarchical structure

To scale,
DNS adopt **three** intertwined hierarchies

naming structure

hierarchy of addresses

<https://www.ee.ethz.ch/de/departement/>

management

hierarchy of authority
over names

infrastructure


hierarchy of DNS servers

naming structure


hierarchy of addresses

<https://www.ee.ethz.ch/de/departement/>


Top Level Domain (TLDs) sit at the top



Domains are subtrees




A name, *e.g.* ee.ethz.ch, represents
a leaf-to-root path in the hierarchy




management

hierarchy of authority
over names


The DNS system is
hierarchically administered





(*) see <http://www.iana.org/domains/root/db>

managed by The Swiss Education & Research Network (*)



(*) see <https://www.switch.ch/about/id/>




Hierarchical administration means
that name collision is trivially avoided


infrastructure

hierarchy of DNS servers

The DNS infrastructure is
hierarchically organized



13 root servers (managed professionally)
serve as root (*)



(*) see <http://www.root-servers.org/>

a. root-servers.net	VeriSign, Inc.
b. root-servers.net	University of Southern California
c. root-servers.net	Cogent Communications
d. root-servers.net	University of Maryland
e. root-servers.net	NASA
f. root-servers.net	Internet Systems Consortium
g. root-servers.net	US Department of Defense
h. root-servers.net	US Army
i. root-servers.net	Netnod
j. root-servers.net	VeriSign, Inc.
k. root-servers.net	RIPE NCC
l. root-servers.net	ICANN
m. root-servers.net	WIDE Project

Ethernet 1000BaseT

PIC5 ON/OFF

0/3 0/2 0/1 0/0

RE-400



PC CARD

RESET

JUNIPER NETWORKS LABEL THIS SIDE

ROUTER.AMS-IX.K.RIPE.NET

K.ROOT-SERVERS.NET

CN714DEBAA

800-08330-06 D0

GIGABIT ETHERNET 0/0

RJ45 EN

AMS-IX

GIGABIT ETHERNET 0/1

RJ45 EN

GIGABIT ETHERNET 0/2

RJ45 EN

SERVICE

CISCO SYSTEMS

CISCO 7301

h.ams-ix.k

1 2 3 6 Link
Mode
12 Link


To scale root servers,
operators rely on **BGP anycast**


Intuition

Routing finds shortest-paths

If several locations announce the same prefix,
then routing will deliver the packets to
the “closest” location

This enables seamless replications of resources





Do you see any problems in
performing load-balancing this way?

Instances of the k-root server (*) are hosted in more than 40 locations worldwide




(*) see k.root-servers.org

Two of these locations are in Switzerland:
in Zürich and in Geneva

Swiss Internet Exchange
ns1.ch-zrh.k.ripe.net

CERN
ns1.ch-gva.k.ripe.net




All locations announce **193.0.14.0/23** in BGP,
with **193.0.14.129** being the IP of the server


Two of these locations are in Switzerland:
in Zürich and in Geneva

Do you mind guessing which one we use, here... in Zürich?


Each instance receives up to 70k queries per second
summing up to more than 4 billions queries per day



TLDs server are also managed professionally by private or non-profit organization




The bottom (and bulk) of the hierarchy is managed by Internet Service Provider or locally



Every server knows the address of the root servers (*)
required for bootstrapping the systems

(*) see <https://www.internic.net/domain/named.root>

Each root server knows
the address of all TLD servers



```
lvanbever:~$ dig @a.root-servers.net ch.
```

ch.	172800	IN	NS	a.nic.ch.
ch.	172800	IN	NS	b.nic.ch.
ch.	172800	IN	NS	c.nic.ch.
ch.	172800	IN	NS	d.nic.ch.
ch.	172800	IN	NS	e.nic.ch.
ch.	172800	IN	NS	f.nic.ch.
ch.	172800	IN	NS	h.nic.ch.

also see <https://www.iana.org/domains/root/db/ch.html>

If you want to learn more on ".ch"
take a look at SWITCH's annual report


REPORT 2020

of the .ch Registry

SWITCH



Any .ch DNS server knows the addresses of the DNS servers of all sub-domains



```
lvanbever:~$ dig @a.nic.ch ethz.ch
```

```
ethz.ch.      3600  IN  NS  ns2.switch.ch.
ethz.ch.      3600  IN  NS  ns2.ethz.ch.
ethz.ch.      3600  IN  NS  ns1.ethz.ch.
```


Once arrived at the leaf of the hierarchy (*.ethz.ch),
each DNS server knows the IP address of all children

```
lvanbever:~$ dig @ns1.ethz.ch comm-net.ethz.ch
```

```
comm-net.ethz.ch. 3600 IN CNAME virt07.ethz.ch.  
virt07.ethz.ch.    3600 IN A  82.130.102.71
```

To scale,
DNS adopt **three** intertwined hierarchies

naming structure

addresses are hierarchical

<https://www.ee.ethz.ch/de/departement/>

management

hierarchy of authority
over names

infrastructure

hierarchy of DNS servers

To ensure availability, each domain must have at least a primary and secondary DNS server

Ensure name service availability
as long as one of the servers is up

DNS queries can be load-balanced
across the replicas

On timeout, client use alternate servers
exponential backoff when trying the same server

Overall, the DNS system is highly scalable, available, and extensible

scalable

#names, #updates, #lookups, #users,
but also in terms of administration

available

domains replicate independently
of each other

extensible

any level (including the TLDs)
can be modified independently

You've founded next-startup.ch and want to host it yourself, how do you insert it into the DNS?

You register next-startup.ch at a registrar *X*
e.g. Swisscom or GoDaddy

Provide *X* with the name and IP of your DNS servers
e.g., [ns1.next-startup.ch,129.132.19.253]

You set-up a DNS server @129.132.19.253
define A records for www, MX records for next-startup.ch...

A DNS server stores Resource Records
composed of a (name, value, type, TTL)

Records

Name

Value

A

hostname

IP address

NS

domain

DNS server name

MX

domain

Mail server name

CNAME

alias


canonical name

PTR

IP address

corresponding hostname

Using DNS relies on two components



DNS query and reply uses UDP (port 53),
reliability is implemented by repeating requests (*)

(*) see Book (Section 5)

DNS resolution can either be
recursive or **iterative**


When performing a **recursive** query,
the client offload the task of resolving to the server


local
DNS server
(dns1.ethz.ch)


root servers


.edu servers

nyu.edu
servers











When performing a **iterative** query,
the server only returns the address of the "next server"





What about resolving speeds?

Waiting for servers all over the globe is not fast...

To reduce resolution times,
DNS relies on caching

DNS servers cache responses to former queries
and your client *and* the applications (!)

Authoritative servers associate a lifetime to each record
Time-To-Live (TTL)

DNS records can only be cached for TTL seconds
after which they must be cleared

As top-level servers rarely change & popular website visited often, caching is **very effective** (*)

Top 10% of names account for 70% of lookups

9% of lookups are unique

Limit cache hit rate to 91%

Practical cache hit rates **~75%**

(*) see <https://pdos.csail.mit.edu/papers/dns:ton.pdf>

Congestion
Control

DNS


Introduction to
2nd project

reliable transport
starts *today!*

Check Tobias' slides on
<https://comm-net.ethz.ch>

Communication Networks

Spring 2021



Laurent Vanbever

nsg.ee.ethz.ch

ETH Zürich (D-ITET)

May 17 2021